


EdgePlus™ Solo ES400

IP Intelligence at the Door Incorporating any Reader for Stand-Alone Applications • 83000B

- ▶ **True Flexibility** - Provides network connectivity for any existing or new Wiegand or compatible HID Clock and Data readers
- ▶ **Management** - Remotely managed over the network via standard web browser
- ▶ **Real Cost Savings** - Network access is CAT-5 for communications and Power over Ethernet (PoE). Eliminates the need for separate power supplies
- ▶ **Established Open Architecture** - Built on the HID OPIN® platform, can be remotely reconfigured to a system reader in a host environment



EDGE™

ACCESS Intelligence @ the Door

The HID EdgePlus™ IP Access Solution puts control and user interface right at the door. The EdgePlus Solo ES400 is a cost-effective, stand-alone, single-door IP access control solution. This easy-to-use solution enables remote management and report generation via standard web browser. User information, administration, door configuration and retrieval of events are done through a user-friendly, instructional web environment. Providing “Intelligence at the Door”, the flexible EdgePlus Solo ES400 offers a wide choice of card reader compatibility. And the EdgePlus Solo ES400 IP Access Solution can be converted from stand-alone operation to a system reader for a host environment quickly and easily through the web browser. There is never a need to go to the door.

With a separately connected reader, EdgePlus is a perfect solution for migrating existing reader installations to the “edge” of the network. Whether the enterprise is iCLASS®, Prox, FlexSmart®, FlexPass®, MIFARE®/DESFire®, CRESCENDO™, or Wiegand output reader, EdgePlus delivers Intelligence at the Door.

Features

- ▶ Embedded User Interface, no external software requirement
- ▶ Remotely managed via standard web browser
- ▶ Web Browser Security - Edge Solo products use SSL 3.0 (Secure Socket Layer) and TLS 3.1 (Transport Layer Security) to establish a secure web browser connection.
- ▶ Works within DHCP or Static IP networks for plug and play installation
- ▶ Multi Language Support - Edge Solo supports the following languages: English, French, German, Spanish (International), Russian, Portuguese (Brazilian), Italian, Chinese (Simplified), Japanese, Korean and Hindi.
- ▶ “Door Dashboard” accesses door commands, status, alarms, and recent events from all screens
- ▶ Back-up and restore of data from user PC
- ▶ Built-in diagnostics
- ▶ Installer “calling card” allows inclusion of contact information for user support
- ▶ User upgradable firmware
- ▶ Built-in help screens
- ▶ Manages 1000 cardholders/credentials
- ▶ Manages 8 schedules and 3 intervals each day of the week including holidays
- ▶ View last 5000 events
- ▶ Standardized report generation, including CSV export
- ▶ Built-in 802.3af Power over Ethernet (PoE), with 700 mA available for external field devices and locking hardware
- ▶ Easily migrates to a host based system - (OEM OR CS)
 - ▶ After upgrade:
 - ▶ 44,000 credentials
 - ▶ 65000 Schedules
 - ▶ Full Edge/VertX® capacities
- ▶ Wet or Dry door relays
- ▶ Permits local laptop computer connections for diagnostics and configuration
- ▶ UL294 Listed - EdgePlus 83000B has UL294 listing when installed with either the HID 6120B iCLASS R40 or 6125B iCLASS RP40 reader. (More readers coming soon)

Mounting

Mount to a single gang style electrical box with two screws. The EdgePlus™ includes tamper protection for this type of installation to secure all wiring within the electrical box. For indoor mounting only.

Easily Interfaced

- RJ-45 connector for Ethernet TCP/IP
- Quick-disconnect screw terminal connectors
- Easily upgrades to a hosted software solution through the network interface

Inputs for

- 1 reader
- 1 door monitor switch
- 1 Request-to-Exit switch
- AC Fail Monitor
- Battery Fail Monitor
- Enclosure Tamper

Non-latching wet/dry relay outputs for

- 1 door strike
- 1 auxiliary device: door held/forced alarm, alarm shunt, host offline (comms down), or general purpose

Cable Specifications

Ethernet	300 feet (100 m) Category 5 cable	ALPHA 9504C ALPHA 9405F
Wiegand	500 feet (150 m) 9-conductor, stranded, overall shield 22 AWG	ALPHA 1299C
Input Circuits	500 feet (150 m) 2-conductor, shielded 22 AWG 18 AWG	ALPHA 1292C ALPHA 2421C
Output Circuits	500 feet (150 m) 2-conductor 22 AWG 18 AWG	ALPHA 1172C ALPHA 1897C
RS-232	50 feet (15 m) 9-conductor, stranded 22 AWG	ALPHA 1299C ALPHA 58119

Minimum wire gauge depends on cable length and current requirements.

Mounting	Single-gang style electrical box
Dimensions	3.3" W x 4.8" H x 1.5" D (83.8 mm x 121.9 mm x 36.3 mm)
Weight	6.8 oz (.195 kg)
Style	Attractive UL94 polycarbonate enclosure protects components from damage and all connections are fully identified by silk-screened nomenclature.
Card Data Formats	Supports any card data format up to 128 bits
Hardware	32-bit RISC CPU, 100 MHz processor
Memory	8 MB onboard Flash memory 32 MB SDRAM 256K SRAM
Visual Indicators	Two LEDs indicate power/network activity and device I/O activity.
Power Supply Requirements	1 A @ 12-16 VDC maximum Recommended: Power is supplied using the Power over Ethernet technology available with PoE (802.3af) enabled network devices. Alternate: Supervised linear power supply with battery backup, input surge protection, and AC Fail and battery low contact outputs. Relays can be configured to supply power as follows: Available Power: The ES400 is capable of supplying a total of 700 mA to field devices. This power may be shared between a reader and one or two additional field devices. Unpowered, relay contacts are rated for 2 A @ 30 VDC Note: Use of a Listed Access Control / Burglary power-limited power supply is required for all Listed installations.
Operating Temperature	The ES400 is intended for use in indoor environments that comply with the following specifications: 32° to 122° F (0° to 50° C)
Operating Humidity	5% to 95% relative, non-condensing
Communication Ports	Ethernet – 10 or 100 Mbps Reader - Wiegand, HID Clock-and-Data
Certifications	UL 294 Listed Component for the US, CSA 205 for Canada, FCC Class A Verification, ICES-003 Class A Canada, EU (CE Marking), Australia (C-Tick Mark), New Zealand
Warranty	Warrantied against defects in materials and workmanship for 18 months (See complete warranty policy for details).

© 2008 HID Global Corporation. All rights reserved. HID, the HID logo, EDGE, EdgeReader, EdgePlus, OPIN, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 3/2008
MKT-ES400_REVb_DS_EN



ACCESS Intelligence @ the Door

hidglobal.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (949) 598-1600
Fax: (949) 598-1690
EDGE Sales Support:
(877) 276.3343

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

